



**IESNA  
SUSTAINING  
MEMBER**



<b>Test Report Number:</b>	<b>LCZP14070106</b>	Total Pages: 7
<b>Applicant Name:</b>	L-TECH CORPORATION	
<b>Applicant Address:</b>	SHAOGANGTOU DISTRICT,QIAOTOU TOWN,DONGGUAN CITY.GUANGDONG PROVINCE,CHINA	
<b>Test item:</b>	LED Downlight	
<b>Model / Type Reference:</b>	LRKT560/563-9030	
<b>Date of Issue:</b>	2014-07-15	
<b>Testing Laboratory:</b>	LCTECH (Zhongshan) Testing Service Co.,Ltd 2/F.,Technology and Enterprise Development Center, Guangyuan Road, Xiaolan, Zhongshan, Guangdong, China	
<b>Test Specification:</b>	Photometric test (According to IES LM-79-08)	
<b>Test Result:</b>	See following pages	
<b>Compiled by:</b>	<b>Reviewed by:</b>	
2014-07-15	Lin Qiu	
2014-07-15	Richard Li	
_____	_____	_____
Date	Name	Signature
Date	Name	Signature
<b>Remark:</b>	N/A	
<p>The duplication of this report or parts of it and its use for advertising purposes is only allowed with permission of the testing laboratory. This report contains the result of the examination of the product sample submitted by the applicant. A general statement concerning the quality of the products from the series manufacture cannot be derived therefore.</p>		



**DESCRIPTION INFORMATION (From Photometric File)**

IESNA:LM-63-1995  
[TEST] LCZP14070106  
[DATE] 2014-7-12  
[MANUFAC] L-TECH CORPORATION  
[LUMCAT] LRKT560/563-9030  
[LUMINAIRE] LED Downlight  
[LAMPCAT] LED  
[LAMP] LED  
[OTHER] ELECTRICAL VALUES:119.95VAC 0.166A 15.43W 0.774

**CHARACTERISTICS**

Total Luminaire Lumens	1097.61
Luminaire Efficacy	71
Total Luminaire Watts	15
CIE Type	Direct
Spacing Criteria (0-180)	1.20
Spacing Criteria (90-270)	1.20
Spacing Criteria (Diagonal)	1.30
Basic Luminous Shape	Circular
Luminous Length (0-180)	0.12 m (Diameter)
Luminous Width (90-270)	0.12 m (Diameter)
Luminous Height	0.00 m

**LUMINANCE DATA (cd/sq.m)**

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	32403	32460	32443
55	27296	27394	27400
65	19674	19766	19794
75	9302	9335	9319
85	4363	4401	4479



**CANDELA TABULATION**



	<b>0</b>	<b>15</b>	<b>30</b>	<b>45</b>	<b>60</b>	<b>75</b>	<b>90</b>
<b>0</b>	475.17	475.17	475.17	475.17	475.17	475.17	475.17
<b>5</b>	472.00	472.67	472.80	473.08	472.67	473.04	471.29
<b>10</b>	464.18	463.97	464.20	464.96	464.80	464.65	463.69
<b>15</b>	451.01	450.98	450.89	450.60	450.96	451.09	450.00
<b>20</b>	431.44	431.94	432.33	432.35	432.54	432.74	431.57
<b>25</b>	408.47	407.92	408.36	409.20	409.12	409.58	408.78
<b>30</b>	380.22	379.94	380.47	380.73	381.11	381.23	380.96
<b>35</b>	348.05	347.73	348.17	348.72	349.08	348.79	348.61
<b>40</b>	312.37	312.00	311.85	311.64	312.57	313.08	312.78
<b>45</b>	272.37	272.03	272.88	272.85	273.40	273.30	272.70
<b>50</b>	229.92	229.86	230.40	230.64	231.13	231.34	231.45
<b>55</b>	186.11	186.33	186.93	186.78	187.38	187.66	186.82
<b>60</b>	141.75	141.93	141.75	142.55	142.49	142.61	143.03
<b>65</b>	98.84	98.74	98.53	99.30	99.72	99.38	99.44
<b>70</b>	60.05	59.88	59.70	60.20	60.23	60.64	60.58
<b>75</b>	28.62	28.80	28.34	28.72	28.56	28.53	28.67
<b>80</b>	11.70	11.73	11.47	11.27	10.89	10.75	10.60
<b>85</b>	4.52	4.60	4.55	4.56	4.65	4.64	4.64
<b>90</b>	1.20	1.19	1.09	0.88	0.70	0.61	0.48
<b>95</b>	0.40	0.40	0.39	0.40	0.39	0.39	0.38
<b>100</b>	0.41	0.40	0.41	0.40	0.42	0.44	0.41
<b>105</b>	0.41	0.42	0.44	0.42	0.46	0.44	0.43
<b>110</b>	0.46	0.47	0.48	0.46	0.46	0.48	0.46
<b>115</b>	0.52	0.48	0.48	0.48	0.51	0.48	0.48
<b>120</b>	0.50	0.49	0.50	0.51	0.52	0.52	0.52
<b>125</b>	0.57	0.57	0.58	0.58	0.57	0.57	0.58
<b>130</b>	0.57	0.61	0.63	0.62	0.61	0.62	0.62
<b>135</b>	0.58	0.59	0.56	0.57	0.58	0.58	0.60
<b>140</b>	0.64	0.64	0.66	0.63	0.64	0.64	0.64
<b>145</b>	0.79	0.80	0.79	0.78	0.79	0.78	0.79
<b>150</b>	0.98	0.99	1.01	1.01	1.00	1.00	0.98
<b>155</b>	1.22	1.22	1.23	1.25	1.24	1.20	1.22
<b>160</b>	1.58	1.55	1.58	1.58	1.55	1.55	1.56
<b>165</b>	1.89	1.88	1.89	1.87	1.92	1.89	1.87
<b>170</b>	2.11	2.14	2.13	2.12	2.14	2.12	2.10
<b>175</b>	2.29	2.25	2.23	2.27	2.26	2.25	2.27
<b>180</b>	2.35	2.35	2.35	2.35	2.35	2.35	2.35



**ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-30	360.04	32.8	32.8
0-40	577.66	52.6	52.6
0-60	954.63	87	87
0-90	1093.31	99.6	99.6
90-120	1.52	.1	.1
90-130	2.02	.2	.2
90-150	2.99	.3	.3
90-180	4.3	.4	.4
0-180	1097.61	100	100

Total Luminaire Efficiency = 100%

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	44.85
10-20	127.07
20-30	188.12
30-40	217.61
40-50	210.08
50-60	166.9
60-70	99.02
70-80	33.85
80-90	5.8
90-100	.57
100-110	.46
110-120	.48
120-130	.51
130-140	.47
140-150	.5
150-160	.57
160-170	.52
170-180	.21

Note: The luminaire was LED luminaire, the luminaire lumens was also considered as bare lamp lumens.




**COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0			
	RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
0	119	119	119	119	119	116	116	116	116	116	111	111	111	111	106	106	106	102	102	102	100
1	110	106	102	99	99	108	104	101	98	100	97	94	96	93	91	92	90	89	87	87	87
2	101	94	88	83	83	99	92	87	82	89	84	80	85	81	78	82	79	76	74	74	74
3	93	84	76	70	70	91	82	75	70	79	73	68	76	71	67	74	70	66	64	64	64
4	86	75	67	60	60	83	73	66	60	71	64	59	69	63	58	66	62	58	56	56	56
5	79	67	59	53	53	77	66	58	52	64	57	52	62	56	51	60	55	51	49	49	49
6	73	61	52	46	46	71	60	52	46	58	51	46	56	50	45	55	49	45	43	43	43
7	68	55	47	41	41	66	55	47	41	53	46	41	52	45	40	50	45	40	38	38	38
8	64	51	43	37	37	62	50	42	37	49	42	37	47	41	36	46	40	36	34	34	34
9	59	47	39	33	33	58	46	39	33	45	38	33	44	38	33	43	37	33	31	31	31
10	56	43	36	30	30	55	43	35	30	42	35	30	41	34	30	40	34	30	28	28	28

Note: The luminaire was LED luminaire, the luminaire lumens was also considered as bare lamp lumens.




Maximum Candela = 475.17 Located At Horizontal Angle = 0, Vertical Angle = 0

# 1 - Vertical Plane Through Horizontal Angles (0 - 180)

# 2 - Vertical Plane Through Horizontal Angles (90 - 270)

Photo of sample



Picture 1 Front View



Picture 2 Back View

--End of test report--