



## ENERGY STAR® Luminaire Test Report

ENERGY STAR® Program Requirements Product Specification for Luminaires - Version 2.0 - Issued 2015-05-29

Prepared For

### L-TECH CORPORATION

Address: Shaogangtou District, Qiaotou Town, Dongguan City, Guangdong, China

Contact Person: Zhenglong Jin, Email: ltech@vip.163.com, phone: 13925742768

Test Laboratory: UL Verification Services (Guangzhou) Co., Ltd.

Test Laboratory Address: Building A1, 1F & 2F, Nansha Science and Technology Innovation Center, No. 25,  
South Huanshi Avenue, Nansha District, Guangzhou 511458, China

Catalog Number

ULD143W-##90, ULD143BZ-##90, ULD143BK-##90

(##=00-11 intends CCT 2700K, 3000K and 3500K, ##=20-30 intends CCT 2700K, 3000K and 4000K.)

Project Number

4788249285

Report Number

4788249285-10a

Test Date

2017-12-12 - 2017-12-24

Issue Date

2018-01-09

Revision Date

N/A

Prepared By

Alvin Xie

Approved By

Dendi Lin

The results contained in this report pertain only to the tested sample.

This report shall not be reproduced, except in full, without written approval of Underwriters Laboratories.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.



## 1.0 Test Summary

ENERGY STAR® Program Requirements Product Specification for Luminaires - Version 2.0 - Issued 2015-05-29

<b>(Under Cabinet Mount)</b>				
Requirement Category	Test Method	Requirement	Test Value	Results (Pass/Fail)
Efficacy (lm/W)	IES LM-79-08	Non-directional: 65 lm/W; Directional: 50 lm/W; Inseparable SSL Luminaire: 70 lm/W.	78.4	Pass
Light Output (lm)	IES LM-79-08	Luminous Flux (lm)	1335.61	Pass
		Under Cabinet: 125 lm/ft	0.00	
Zonal Lumen Density	IES LM-79-08	For directional luminaires only. (0°~60°C) >60%	78.70%	Pass
CCT (K)	ANSI C78.377-2011	fall within the corresponding 7-step chromaticity quadrangles	2777	Pass
CRI	IES LM-79-08, CIE 13.3-1995	Ra ≥ 80	93.3	Pass
R9	IES LM-79-08, CIE 13.3-1995	R9 > 0	59	Pass
Color Angular Uniformity	IES LM-79-08, CIE 15: 2004	≤ 0.006 on the CIE 1976 (u',v') diagram	0.00091	Pass
Lumen Maintenance & Light Source Life (hours)	IES LM-80-08*, IES TM-21-11*	L70 ≥ 25,000 hours for indoor; L70 ≥ 35,000 hours for outdoor; L70 ≥ 50,000 h for inseparable luminaires	60000	Pass
Color Maintenance	IES LM-80-08*, IES LM-84-14	≤ 0.007 on the CIE 1976 (u',v') diagram	0.0031	Pass
Source Start Time (ms)	ENERGY STAR Start Time Test Method	1 s for connected luminaires; 750 ms for other luminaires.	80.8	Pass
Source Run-Up Time (s)	ENERGY STAR Run Up Time Test Method	≤ 45 seconds	N/A	N/A
Power Factor	C82.77-10:2014	power ≤ 5 watts: PF ≥ 0.5; power > 5 watts: PF ≥ 0.7	0.983	Pass
Transient Protection	IEEE C62.41.2-2002	Survival	Validated	Pass
Standby Power Consumption (W)	IEC 62301 ED.2.0 B	Shall not draw power in the off state.	0.01	Pass
Operating Frequency (Hz)	N/A	Frequency ≥ 120 Hz	120.2	Pass

\* The standards are NOT covered by the NVLAP scope of test laboratory UL Verification Services (Guangzhou) Co., Ltd.



## 1.0 Test Summary (Cont'd)

Requirement Category	Test Method	Requirement	Test Value	Results (Pass/Fail)
Light Source Replaceability	N/A	Fluorescent & Directional LED luminaire	Validated	Pass
LED Tc Temperature (°C)	ANSI/UL 153:2002 ANSI/UL 1598:2008	Within the highest test temperature in LM-80 report	38.9	Pass
Driver Case Temperature (°C)	ANSI/UL 153:2002 ANSI/UL 1598:2008	≤ TMPC marked on the the driver	57.4	Pass
Recessed Downlight Thermal Performance	ANSI/UL 1598-2008 ASTM E283-04*	Insulation contact & Airtight construction	N/A	N/A
SAFETY REQUIREMENTS for luminaire and driver	UL Safety standards	Safety documentation	Validated	Pass
Dimming: Range (Minimum)	N/A	≤20%	4.91%	Pass
Dimming: Noise	N/A	24dBA at 1 meter	17.8	Pass
Labeling & Packaging	N/A	Relevant document	Validated	Pass
WARRANTY REQUIREMENTS	N/A	no less than 3 years	Validated	Pass
Lighting Toxics Reduction Requirements	RoHS Directive, 2003*	Relevant Documentations	Validated	Pass

\* The standards are NOT covered by the NVLAP scope of test laboratory UL Verification Services (Guangzhou) Co., Ltd.



## 2.0 Test List

Test Item	Test	Test Date	Test Model	Tests Conducted By
1	Integrating Sphere Test	2107-12-19	ULD143W-0190	Lily Chen
		2107-12-24	ULD143W-2090	Lily Chen
2	Goniophotometer Test	2107-12-12	ULD143W-0190	Lily Chen
3	Color Angular Uniformity	2107-12-18	ULD143W-0190	Lily Chen
4	Source Start Time & Run-Up time	2107-12-13	ULD143W-0190	Lily Chen
5	Operating Frequency Test	2107-12-13	ULD143W-0190	Lily Chen
6	Transient Protection Test	2107-12-19	ULD143W-0190	Lily Chen
7	Standby Power Consumption	2107-12-19	ULD143W-0190	Lily Chen
8	Dimming Test	2107-12-19	ULD143W-0190	Lily Chen
9	In-Situ Temperature Measurement Test	2107-12-19	ULD143W-0190	Lily Chen

### Remark (if any)

1, UL test equipment information is recorded on Meter Use in UL's Aurora database.  
2, The product belong to Color Tunable, where ##=00-11 intends CCT 2700K, 3000K and 3500K, ##=20-30 intends CCT 2700K, 3000K and 4000K. The default settings and maximum power are at 2700K color temperature states.



### 3.0 Production Description

**Luminaire Description:** Indoor Directional Luminaires, LED Under cabinet for Color Tunable  
120Vac, 60Hz, 18W, CRI 90, CCT 2700K - 4000K, Length 42 inch


**Lighting Source:** 2T03X2WWxx000xxx made by Edison Opto Corporation

**Mounting:** Under Cabinet Mount

**LED Driver:** ULD14-16

**Family Model and Variation:** ULD143W-##90, ULD143BZ-##90, ULD143BK-##90, W, BZ and BK intends the color of product appearance, W=White, BZ=Brown, BK=Black, ##=00-11 intends CCT 2700K, 3000K and 3500K; ##=20-30 intends CCT 2700K, 3000K and 4000K. All of the CCT corresponding LED is 0.2 W series model 2T03X2WWxx000xxx except the model name with ##=20-30 of CCT 2700K products use LED is 0.5W series model 2T03X5WWxx000xxx.

#### Photos of Luminaire Characteristics





## 4.0 Photometric Measurements

### 4.1 Integrating Sphere Test

Model No.	ULD143W-0190	Sample ID.	1298529-S001	Temperature (°C)	25.1
Operate time (Min.)	50	Stabilization time (Min.)	45		



#### Test Method

1. The sample was tested according to the IES LM-79-2008.
2. Photometric parameters were measured using an integrating sphere, a spectroradiometer and software. The ambient temperature inside the sphere was maintained at  $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$ .
3. The sample measurements were made using a spectroradiometer connected by a fiber optic cable and detector through the detector port of the integrating sphere. The sample was operated at 120 Volts AC, 60Hz. It was stabilized before measurement was made. Chromaticity coordinates, correlated color temperature and color rendering index were calculated from the spectral radiant flux measurements taken at 5 nm intervals over the range of 380 to 780 nm.

#### Integrating Sphere Conditions and Results

Model Number	Orientation	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	CCT (K)	CRI (Ra)	R9	Luminous Flux (lm)	Luminous Efficacy (lm/W)
ULD143W-0190	Horizontal	120.01	60	0.144	17.03	0.983	2777	93.3	59	1335.61	78.4

Spectroradiometric Parameters





## 4.0 Photometric Measurements

### 4.2 Integrating Sphere Test

Model No.	ULD143W-2090	Sample ID.	1291153-S001	Temperature (°C)	25.1
Operate time (Min.)	50	Stabilization time (Min.)	45		



#### Test Method

1. The sample was tested according to the IES LM-79-2008.
2. Photometric parameters were measured using an integrating sphere, a spectroradiometer and software. The ambient temperature inside the sphere was maintained at  $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$ .
3. The sample measurements were made using a spectroradiometer connected by a fiber optic cable and detector through the detector port of the integrating sphere. The sample was operated at 120 Volts AC, 60Hz. It was stabilized before measurement was made. Chromaticity coordinates, correlated color temperature and color rendering index were calculated from the spectral radiant flux measurements taken at 5 nm intervals over the range of 380 to 780 nm.

#### Integrating Sphere Conditions and Results

Model Number	Orientation	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	CCT (K)	CRI (Ra)	R9	Luminous Flux (lm)	Luminous Efficacy (lm/W)
ULD143W-2090	Horizontal	120	60	0.146	17.12	0.98	2748	92.9	57	1477.31	86.3

Spectroradiometric Parameters





## 5.0 Photometric Measurements

### 5.1 Goniophotometer Test

Model No.	ULD143W-0190	Sample ID.	1298529-S001
Operate time (Min.)	90	Stabilization time (Min.)	45

#### Test Method

1. The sample was tested according to the IES LM-79-2008.
2. Photometric parameters were measured using a type C goniophotometer and software.
3. The ambient temperature shall be maintained at  $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$ , measured at a point not more than 1 m from the sample and at the same height as the sample.
4. The samples were operated at rated voltage and was stabilized before measurement. Luminous flux, luminaire efficacy, zonal lumen were calculated from the software taken at  $1^{\circ}$  vertical intervals and  $22.5^{\circ}$  horizontal intervals.

#### Goniophotometer Test Conditions

Temperature ( $^{\circ}\text{C}$ )	Voltage (Vac)	Frequency	Current (A)	Power (W)	Power Factor	Orientation
25	119.97	60	0.1449	17.082	0.9826	Horizontal

#### Test Results


Flux (lm)	Zonal Lumen Requirement (0-60 $^{\circ}$ )	Field Angle (10%)		Beam Angle (50%)		Luminous Efficacy (lm/W)
		Horizontal Spread	Vertical Spread	Horizontal Spread	Vertical Spread	
1,338.30	78.70%	163.8	160.7	104.8	97.8	78.3






## 5.1 Goniophotometer Test (Cont'd)

### Light Distribution Curve



### Isolux Plot





## 5.1 Goniophotometer Test (Cont'd)

### Zonal Lumen Summary

#### **Zonal Lumen Summary**

Zone	Lumens	% Luminaire
0-30	381.9	28.5%
0-40	616.2	46%
0-60	1,053.4	78.7%
60-90	275.4	20.6%
70-100	134.7	10.1%
90-120	8.4	0.6%
0-90	1,328.8	99.3%
90-180	9.5	0.7%
0-180	1,338.3	100%

### Lumens Per Zone

#### **Lumens Per Zone**

Zone	Lumens	% Total	Zone	Lumens	% Total
0-5	11.9	0.9%	90-95	6.5	0.5%
5-10	35.3	2.6%	95-100	1.4	0.1%
10-15	57.4	4.3%	100-105	0.1	0%
15-20	77.1	5.8%	105-110	0.1	0%
20-25	93.8	7.0%	110-115	0.1	0%
25-30	106.4	8.0%	115-120	0.1	0%
30-35	115.0	8.6%	120-125	0.1	0%
35-40	119.2	8.9%	125-130	0.1	0%
40-45	119.2	8.9%	130-135	0.1	0%
45-50	115.2	8.6%	135-140	0.1	0%
50-55	107.1	8.0%	140-145	0.1	0%
55-60	95.8	7.2%	145-150	0.1	0%
60-65	82.0	6.1%	150-155	0.1	0%
65-70	66.5	5.0%	155-160	0.1	0%
70-75	50.5	3.8%	160-165	0.1	0%
75-80	36.2	2.7%	165-170	0.1	0%
80-85	25.1	1.9%	170-175	0.0	0%
85-90	15.0	1.1%	175-180	0.0	0%



## 5.1 Goniophotometer Test (Cont'd)

### Candela Table - Type C

	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5	360
0	499	499	499	499	499	499	499	499	499	499	499	499	499	499	499	499	499
1	510	499	499	499	499	499	499	499	510	499	499	499	499	499	499	499	510
2	510	499	499	499	499	499	499	499	510	499	499	499	499	499	499	499	510
3	509	498	498	498	499	498	498	498	509	498	498	498	499	498	498	498	509
4	508	497	497	498	498	498	497	497	508	497	497	498	498	498	497	497	508
5	506	496	496	497	498	497	496	496	506	496	496	497	498	497	496	496	506
6	505	495	495	497	497	497	495	495	505	495	495	497	497	497	495	495	505
7	503	493	493	496	496	496	493	493	503	493	493	496	496	496	493	493	503
8	501	491	491	495	495	495	491	491	501	491	491	495	495	495	491	491	501
9	498	489	489	493	493	514	517	520	498	489	489	493	493	474	460	458	484
10	496	487	487	492	492	492	487	487	496	487	487	492	492	492	487	487	496
11	493	484	484	491	490	491	484	484	493	484	484	491	490	491	484	484	493
12	490	482	482	489	489	489	482	482	490	482	482	489	489	489	482	482	490
13	486	479	479	487	487	487	479	479	486	479	479	487	487	487	479	479	486
14	482	475	476	485	485	485	476	475	482	475	476	485	485	485	476	475	482
15	478	472	472	483	483	483	472	472	478	472	472	483	483	483	472	472	478
16	474	469	469	481	481	481	469	469	474	469	469	481	481	481	469	469	474
17	470	464	465	478	478	478	465	464	470	464	465	478	478	478	465	464	470
18	465	460	461	475	476	475	461	460	465	460	461	475	476	475	461	460	465
19	460	456	457	472	473	472	457	456	460	456	457	472	473	472	457	456	460
20	455	451	453	469	470	469	453	451	455	451	453	469	470	469	453	451	455
25	428	425	428	447	450	447	428	425	428	425	428	447	450	447	428	425	428
30	397	396	401	419	424	419	401	396	397	396	401	419	424	419	401	396	397
35	363	363	370	387	394	387	370	363	363	363	370	387	394	387	370	363	363
40	327	329	337	351	360	351	337	329	327	329	337	351	360	351	337	329	327
45	290	293	303	315	324	315	303	293	290	293	303	315	324	315	303	293	290
50	251	256	264	276	284	276	264	256	251	256	264	276	284	276	264	256	251
55	213	219	223	239	241	239	223	219	213	219	223	239	241	239	223	219	213
60	175	181	184	200	200	200	184	181	175	181	184	200	200	200	184	181	175
65	138	144	147	159	159	159	147	144	138	144	147	159	159	159	147	144	138
70	103	108	111	122	121	122	111	108	103	108	111	122	121	122	111	108	103
75	75	76	79	89	86	89	79	76	75	76	79	89	86	89	79	76	75
80	54	51	55	61	59	61	55	51	54	51	55	61	59	61	55	51	54
85	36	33	35	41	40	41	35	33	36	33	35	41	40	41	35	33	36
90	20	17	17	20	21	20	17	17	20	17	17	20	21	20	17	17	20
95	8	6	5	6	6	6	5	6	8	6	5	6	6	6	5	6	8
100	1	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1
105	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
110	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
115	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
120	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
125	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
130	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
135	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
140	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
145	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
150	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
155	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
160	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
165	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
170	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
175	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
180	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0



## 5.0 Photometric Measurements

### 5.2 Color Angular Uniformity

Model No.	ULD143W-0190	Sample ID.	1298529-S001
-----------	--------------	------------	--------------

#### Test Method

1. The sample was tested according to the IES LM-79-2008.
2. Photometric parameters were measured using a type C goniophotometer and software.
3. The ambient temperature shall be maintained at  $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$ , measured at a point not more than 1 m from the sample and at the same height as the sample.
4. The sample was operated at 120 Volts AC, 60Hz. It was stabilized before measurement was made. Color spatial uniformity was calculated from the software taken at  $1^{\circ}$  vertical intervals and  $90^{\circ}$  horizontal intervals.

#### Test Results

Temperature (°C)	Voltage (Vac)	Frequency	Current (A)	Power (W)	Maximum $\Delta u'v'$
25.1	120.01	60	0.145	17.13	0.00091



## 6.0 Electrical Test

### 6.1 Source Start Time & Run-Up time


Model No.	ULD143W-0190	Sample ID.	1298529-S001
-----------	--------------	------------	--------------

#### Test Method

1. The sample was tested according to ENERGY STAR Start Time Test and ENERGY STAR Run-Up Time Test for fluorescent luminaires only.
2. Each test sample was operated in its designated orientation at rated input voltage in a  $25 \pm 5^\circ \text{C}$  ambient. A photodetector is used to monitor the luminaire light output. Time was recorded when the sample was fully illuminated and reached 90% of stabilized lumen output.

#### Test Results

Temperature (°C)	Voltage (Vac)	Frequency	Start Time (ms)	Run-Up time (s)
25.2	120	60	80.8	N/A





## 6.0 Electrical Test

### 6.2 Operating Frequency Test


Model No.	ULD143W-0190	Sample ID.	1298529-S001
-----------	--------------	------------	--------------

#### Test Method

1. The sample was tested according to ANSI C82.2-2002 for fluorescent luminaires.
2. Each test sample was operated at rated input voltage. Light output waveform shall be measured with a photodetector, transimpedance amplifier and oscilloscope. The AC ripple on the output DC line was measured and recorded by the oscilloscope according to Energy Star directions.

#### Test Results

Temperature (°C)	Voltage (Vac)	Frequency	Operating Frequency (Hz)
25.1	121	60	120.2





## 6.0 Electrical Test

### 6.3 Transient Protection Test

Model No.	ULD143W-0190	Sample ID.	1298529-S001
-----------	--------------	------------	--------------

#### Test Method

The transient protection tests at ambient temperature were performed on one sample. Each sample was operated at rated input voltage in the specific orientation during the tests. A test system with an 100kHz Ring Wave Module and a Coupler/Decoupler Module was used to generate the 2500 volt ring wave transient strike across the luminaire contacts. Each wave consisted of a 0.5 microsecond rise time. Seven strikes were performed on each sample in accordance with ANSI/IEEE C62.41 (Category A): Recommended Practice on Surge Voltages in Low – Voltage AC Circuits.

#### Test Results

Temperature (°C)	Voltage (Vac)	Frequency	After Test - Seven Strikes (Survival/Dead)
25	120.1	60	Survival



## 6.0 Electrical Test

### 6.4 Standby Power Consumption

Model No.	ULD143W-0190	Sample ID.	1298529-S001
-----------	--------------	------------	--------------

#### Test Method

A sample was tested according to the IEC 62301-2011 Edition 2. The sample was operated at rated voltage and frequency, working in the active and standby mode\*. For loads greater than or equal to 10 W, at least three significant figures shall be reported. After stability, the electrical parameter would be measured using proper method\*\* and the value of  $U_e$ \*\*\* was calculated according to the Annex D. The test results shall be compliant with the relative requirements#.

#### Test Results

Temperature (°C)	Mode	Voltage (Vac)	Frequency	Current (mA)	Power Factor	Standby Power (W)
25.1	Standby mode	120	60	0.092	0.904	0.01

\* The working mode is controlled stably by the light sensor. When environment gets dim, it works in active mode. If not, it works in standby mode. The sample was tested under different illuminance to change mode.

\*\* The sample was tested with direct meter reading method according to IEC 62301-2011 Section 5.3.4.

\*\*\* The uncertainty of the test equipment (Power Analyzer)  $U_e$  is equal to 0.2% ( $K=2$ , at the 95% confidence level).

# As  $U_e$  is no greater than the permitted value  $U_{ma}$  specified in IEC 62301-2011 Section 4.4.1, the measurement is acceptable.





## 6.0 Electrical Test

### 6.5 Dimming Test

Model No.	ULD143W-0190	Sample ID.	1298529-S001
-----------	--------------	------------	--------------

#### Dimmer Information

Manufacture	Lutron	Model Number	DVCL-153P
Rated for CFL / LED	LED	Technology / Features	Forward phase-cut

#### Test Method

1. The test was performed using a relative photometry method, according to ENERGY STAR Recommended Practice - Light Output on a Dimmer and ENERGY STAR<sup>®</sup> Recommended Practice - Noise.
2. The measurement was taken one test sample combined with the dimmers. The sample was tested at the rated electrical parameter, and allowed to stabilize and verify by taking light output measurements every minute, until consecutive measurements are no more than 0.5% apart.
3. The noise test shall be conducted on sample in the sound chamber with one microphone. The microphone was located in six position to get the peak noise.

#### Test Results

Temperature (°C)	Voltage (Vac)	Frequency	Baseline Light Output (lx)		Maximum Light Output (lx)	Minimum Light Output (lx)
25.1	120	60	886		780	43.5
Ambient Sound (dBA)	Peak Noise at BLO (dBA)	Peak Noise at MaxLO (dBA)	Peak Noise at MinLO (dBA)	Position (degree)	Maximum Light Output Ratio (%)	Minimum Light Output Ratio (%)
17.7	17.8	17.8	17.8	N/A	88.04%	4.91%



## 7.0 In-Situ Temperature Measurement Test

Model No.	ULD143W-0190	Sample ID.	1298529-S001
-----------	--------------	------------	--------------

### Test Method

1. In-Situ Temperature Measurement Test is conducted according to the UL1598-2008, Section 14 or UL 153-2002, Sections 124.
2. The testing was conducted in a room with ambient temperature of  $25^{\circ}\text{C} \pm 5^{\circ}\text{C}$ . The apparatus construction followed those described in UL1598-2008 for normal temperature testing. Thermocouples were placed on the LED package in the locations indicated by LM-80 report. The temperature was recorded after the lamp was operating for a minimum of 7.5 hours.

### In-Situ Temperature Measurement Test Conditions

Temperature	Voltage (Vac)	Frequency	Current (A)	Power (W)	Power Factor	Orientation
22.4	120.01	60	0.144	17.03	0.983	Face Down

### Test Results



Thermocouple Location	Customer claim Current (mA)	Temperature for Lighting source ( $^{\circ}\text{C}$ )		LED Model Number	LM-80 Limit Current (mA)	LM-80 Limit Temp. ( $^{\circ}\text{C}$ )
		Test result column 1	Test result (Correct to $25^{\circ}\text{C}$ )			
TMP of LEDs	60	36.3	38.9	2T03X2WWxx00 0xxx	60	85
Ambient temperature	N/A	22.4	25.0			

Thermocouple Location	Temperature for LED driver ( $^{\circ}\text{C}$ )		LED driver Model Number	LED Driver Tc Temp. ( $^{\circ}\text{C}$ )
	Test result column 1	Test result (Correct to $25^{\circ}\text{C}$ )		
TMP of LED drivers	54.8	57.4	ULD14-16	90
Ambient temperature	22.4	25.0		





## 7.0 In-Situ Temperature Measurement Test (Cont'd)

### Test Photos for LEDs



### Test Photos for LED Drivers





\*\*\*\*\* END OF REPORT. THIS PAGE INTENTIONALLY LEFT BLANK \*\*\*\*\*