

LRKT207-5CCT 2 inch LED Retrofit

2" Round Gimbal LED Downlight Retrofit Kit



- Finishes



B - Black



BZ - Bronze



SN - Satin Nickel



Use the switch to set the desired CCT (Correlated Color Temperature).



SPECIFICATION

QUICK FEATURES

- Cast aluminum trim routes heat away from electrical components
- 4 different colors : **W**-White / **B**-Black / **SN**-Satin Nickel / **BZ**-Bronze
- 5 Position CCT Selectable switch (2700K / 3000K / 3500K / 4000K / 5000K)
- Dimmable to 10% with most standard triac dimmers
- cUL classified / ENERGY STAR qualified
- Damp Location
- Lifetime of 50,000 hours
- 5 year warranty

PERFORMANCE DATA

Input Voltage	120V
Frequency	50 / 60Hz
T Ambient	-30°C ~40°C (-22°F ~104°F)

(all values at 25°C without a dimming control in circuit)

LIGHT SOURCE TEST TABLE


Wattge	2700K	3000K	3500K	4000K	5000K
8 W	770 lm	800 lm	840 lm	850 lm	820 lm

CRI 90

DIMENSINONS



Select 5 kinds of CCT



ORDERING INFORMATION

5 CCT Selectable

Model No.	Description
LRKT207W-5CCT	2" LED Retrofit / Round Gimbal / White
LRKT207B-5CCT	2" LED Retrofit / Round Gimbal / Black
LRKT207SN-5CCT	2" LED Retrofit / Round Gimbal / Satin Nickel
LRKT207BZ-5CCT	2" LED Retrofit / Round Gimbal / Bronze

DIMMING LIST

List of Triac Dimmer Switch (120V)

Mfr	Model #	Dimming Rate
COOPER	DLC03P	10 - 100%
Leviton	1A1505 / 1C1605	10 - 100%
Leviton	6631 / 6633	10 - 100%
Lutron	CT-603PG / CT-600PR	10 - 100%
Lutron	DV-600PR / DV603PG	10 - 100%
Lutron	DVW-603PGH / DVCL-153P	10 - 100%
Lutron	MACL-153M / TGCL-153P	10 - 100%
Lutron	S-600PR / S-2-LH	10 - 100%