# L - TECH®

Project:
Fixture Type:
Location:
Contact/Phone:

The LRKT403NC is 4 inch Non-class 2 driver and diecast body of LED Retrofit Kit with Baffle. It is compatible with most of 4 inch standard recessed new construction and remodel housings. The Retrofit Kit comes with a E26 medium screw-base Edison adaptor for easy installation into standard incandescent sockets.

### **DESCRIPTION**

- Diecast aluminum heatsink dissipates heat from the LED board.
- 4 different colors for trim White, Black, Bronze, Satin Nickel.
- 3 Tension clips pre-installed on unit for easy installation.
- E26 medium screw-base Edison adaptor provides easy installation into Incandescent housings.
  (GU10 and GU24 socket adaptor available - sold separately)

#### LED LIGHT ENGINE

- Protected LED driver performs at 120V.
- Dimming down to 10% with most dimmers.
- CCT 2700K, 3000K, 4000K, 5000K available
- CRI ≥80 or ≥90
- Long life LED chips guaranteed up to 50,000 hours.

### **WARRANTY**

Guaranteed five years from the purchase date of the product, against mechanical defects in manufacturing.

# LISTINGS

- cULus classified
- Energy star qualified
- Title 24 compliant
- Wet locations (Not suitable for coastal/salt water area)
- Damp locations
- RoHS compliances
- Tested in accordance with IESNA LM79 & LM80

#### **PERFORMANCE DATA**

Input Voltage	120V	
Input Power	11W	
Frequency	50 / 60Hz	
CRI	90	
T Ambient	-30℃~40℃ (-22°F~104°F)	
ССТ	3000 K	
Lumens	700 lm	

(all values at 25°C without a dimming control in circuit)

# LRKT403NC

4" Non-class 2 Driver & Diecast Body LED Baffle Retrofit Kit












## **DIMENSIONS**



# **PRODUCT CODES**

Model NO.	Description
LRKT403NC-W	4" LED Retrofit / Baffle / White
LRKT403NC-B	4" LED Retrofit / Baffle / Black
LRKT403SNC-SN	4" LED Retrofit / Baffle / Satin Nickel
LRKT403NC-BZ	4" LED Retrofit / Baffle / Bronze

	List of Triac Dimmer Switc	h
Mfr	Model #	Dimming Rate
COOPER	DLC03P	10 - 100%
Leviton	1A1505 / 1C1605	10 - 100%
Leviton	6631 / 6633	10 - 100%
Lutron	CT-603PG / CT-600PR	10 - 100%
Lutron	DV-600PR / DV603PG	10 - 100%
Lutron	DVW-603PGH / DVCL-153P	10 - 100%
Lutron	MACL-153M / TGCL-153P	10 - 100%
Lutron	S-600PR / S-2-LH	10 - 100%

