


LRKT411EN-5CCT Selectable 5 CCT

4" Round Gimbal LED Downlight Retrofit Kit - New Version




DIMENSIONS



Use the switch to set the desired CCT (Correlated Color Temperature).

Selectable 5 CCT Switch



- Finishes



B - Black



BZ - Bronze



SN - Satin Nickel

SPECIFICATION

QUICK FEATURES

- Diecast construction provides lasting durability
- Adjustable gimbal offers 22-degree tilt and up to 355-degree rotation
- 4 different colors : **W**-White / **B**-Black / **SN**-Satin Nickel / **BZ**-Bronze
- 5 Position CCT Selectable switch (2700K / 3000K / 3500K / 4000K / 5000K)
- Dimmable to 10% with most standard triac dimmers
- E26 medium screw-base Edison adaptor provides easy installation into Incandescent housings (GU10 and GU24 socket adaptor available - sold separately)
- cUL classified / ENERGY STAR qualified
- Damp Location
- Lifetime of 50,000 hours
- 5 year warranty

PERFORMANCE DATA

Input Voltage	120V
Frequency	50 / 60Hz
T Ambient	-30 °C ~ 40 °C (-22 °F ~ 104 °F)

(all values at 25°C without a dimming control in circuit)

LIGHT SOURCE TEST TABLE

Wattge	2700K	3000K	3500K	4000K	5000K
8 W	640 lm	660 lm	670 lm	690 lm	700 lm
CRI 90					

ORDERING INFORMATION

5 CCT Selectable

Model No.	Description
LRKT411W-EN-5CCT	4" LED Retrofit / Round Gimbal / White
LRKT411B-EN-5CCT	4" LED Retrofit / Round Gimbal / Black
LRKT411SN-EN-5CCT	4" LED Retrofit / Round Gimbal / Satin Nickel
LRKT411BZ-EN-5CCT	4" LED Retrofit / Round Gimbal / Bronze

DIMMER LIST

List of Triac Dimmer Switch (120V)

Mfr	Model #	Dimming Rate
COOPER	DLC03P	10 - 100%
Leviton	1A1505 / 1C1605	10 - 100%
Leviton	6631 / 6633	10 - 100%
Lutron	CT-603PG / CT-600PR	10 - 100%
Lutron	DV-600PR / DV603PG	10 - 100%
Lutron	DVW-603PGH / DVCL-153P	10 - 100%
Lutron	MACL-153M / TGCL-153P	10 - 100%
Lutron	S-600PR / S-2-LH	10 - 100%



L-TECH CORPORATION
www.L-Techcorp.com

CHINA : SHAOGANGTOU DISTRICT, QIAOTOU TOWN, DONGGUAN CITY, GUANGDONG 523536
TEL : 86-769-83423455 / FAX : 86-769-83423173 E-mail : ltech@vip.163.com

KOREA : A-1804, WOOLIM BLUE NINE, 240-21, YEOMCHANG-DONG, GANGSEO-GU, SEOUL, 157-779
TEL : 82-2-2666-2917~8 / FAX : 82-2-2666-7052 E-mail : ltech77@ltechcorp.com