


4 inch LED Retrofit

4" Round Deep Smooth LED Downlight Retrofit Kit



Dimensions



Finishes



SPECIFICATION

QUICK FEATURES

- Spun aluminum trim routes heat away from electrical components
- 4 different colors : **W**-White / **B**-Black / **SN**-Satin Nickel / **BZ**-Bronze
- Dimmable to 10% with most standard triac dimmers
- E26 medium screw-base Edison adaptor provides easy installation into Incandescent housings (GU10 and GU24 socket adaptor available - sold separately)
- cUL classified / ENERGY STAR qualified
- Wet Location
- Lifetime of 50,000 hours
- 5 year warranty

PERFORMANCE DATA

Input Voltage	120V
Frequency	50 / 60Hz
T Ambient	-30°C ~40°C (-22°F~104°F)

(all values at 25°C without a dimming control in circuit)

LIGHT SOURCE TEST TABLE

Wattge	2700K	3000K	4000K	5000K
11 W	790 lm	800 lm	820 lm	840 lm

CRI 90

ORDERING INFORMATION

Model NO.	Description
LRKT419W-EN	4" LED Retrofit / Round Deep Smooth / White
LRKT419W-B	4" LED Retrofit / Round Deep Smooth / Black
LRKT419W-SN	4" LED Retrofit / Round Deep Smooth / Satin Nickel
LRKT419W-BZ	4" LED Retrofit / Round Deep Smooth / Bronze

DIMMER LIST

List of Triac Dimmer Switch (120V)

Mfr	Model #	Dimming Rate
COOPER	DLC03P	10 - 100%
Leviton	1A1505 / 1C1605	10 - 100%
Leviton	6631 / 6633	10 - 100%
Lutron	CT-603PG / CT-600PR	10 - 100%
Lutron	DV-600PR / DV603PG	10 - 100%
Lutron	DVW-603PGH / DVCL-153P	10 - 100%
Lutron	MACL-153M / TGCL-153P	10 - 100%
Lutron	S-600PR / S-2-LH	10 - 100%