


LRKT449EN-5CCT Selectable 5 CCT

4" Square Baffle LED Downlight Retrofit Kit - New Version




DIMENSINONS



Use the switch to set the desired CCT (Correlated Color Temperature).

Selectable 5 CCT Switch



- Finishes



B - Black



BZ - Bronze



SN - Satin Nickel

SPECIFICATION

QUICK FEATURES

- Diecast construction provides lasting durability
- 4 different colors : **W**-White / **B**-Black / **SN**-Satin Nickel / **BZ**-Bronze
- 5 Position CCT Selectable switch (2700K / 3000K / 3500K / 4000K / 5000K)
- Dimmable to 10% with most standard triac dimmers
- E26 medium screw-base Edison adaptor provides easy installation into Incandescent housings (GU10 and GU24 socket adaptor available - sold separately)
- cUL classified / ENERGY STAR qualified
- Wet Location
- Lifetime of 50,000 hours
- 5 year warranty

PERFORMANCE DATA

Input Voltage	120V
Frequency	50 / 60Hz
T Ambient	-30 °C ~ 40 °C (-22 °F ~ 104 °F)

(all values at 25°C without a dimming control in circuit)

LIGHT SOURCE TEST TABLE

Wattge	2700K	3000K	3500K	4000K	5000K
10 W	730 lm	740 lm	750 lm	770 lm	780 lm

CRI 90

ORDERING INFORMATION

5 CCT Selectable

Model No.	Description
LRKT449W-EN-5CCT	4" LED Retrofit / Square Baffle / White
LRKT449B-EN-5CCT	4" LED Retrofit / Square Baffle / Black
LRKT449SN-EN-5CCT	4" LED Retrofit / Square Baffle / Satin Nickel
LRKT449BZ-EN-5CCT	4" LED Retrofit / Square Baffle / Bronze

DIMMER LIST

List of Triac Dimmer Switch (120V)

Mfr	Model #	Dimming Rate
COOPER	DLC03P	10 - 100%
Leviton	1A1505 / 1C1605	10 - 100%
Leviton	6631 / 6633	10 - 100%
Lutron	CT-603PG / CT-600PR	10 - 100%
Lutron	DV-600PR / DV603PG	10 - 100%
Lutron	DVW-603PGH / DVCL-153P	10 - 100%
Lutron	MACL-153M / TGCL-153P	10 - 100%
Lutron	S-600PR / S-2-LH	10 - 100%