L - TECH[®]

LED Downlight Square 8 inch

8" Square LED Recessed Downlight Fram & Trim



- IC Rated
- Thermally protected, high efficiency driver standard
- Available at 120-277V

QUICK FEATURES

- Dimmable to 10% with most standard 0-10V dimmers
- 5 position CCT Selectable switch (2700K / 3000K / 3500K / 4000K / 5000K)
- cUL classified / ENERGY STAR qualified
- Lifetime of 50,000 hours
- 5 year warranty


PERFORMANCE DATA

Input Voltage	120-277V
Frequency	50 / 60Hz
T Ambient	-30℃~40℃ (-22°F~104°F)

(all values at 25°C without a dimming control in circuit)

FRAME






Features

- Galvanized steel construction plaster frame-in with Junction box captive hanger bar with real nail.
- Contains seven 7/8" knockouts
- Four plastic Romex cable Trap Using protect and easily installation of Romex cable
- LED Driver is mounted directly on the frame. - 18 Watt : 120-277V (0-10V dimming)

SQUARE TRIM



Dimension



Features

- Square trim consists of a plastic ring and an aluminum stamping body.
- · Soft white lens provides smooth lumen distribution and eliminates LED pixelation.
- Use select 5 kinds of CCT with a switch on the connector.
- · Easy installation with Ideal connector and Torsion spring.

Light Source Test Table

Wattge	2700K	3000K	3500K	4000K	5000K
18 W	1480 lm	1500 lm	1530 lm	1550 lm	1560 lm
					CRI 90

ORDERING INFORMATION

1 CCT		
Model No.	Description	
LED8SQ	8" LED Square Frame / Driver connected to J-Box / 18W / 120-277V / 0-10V Dimming	
LTSQ801	8" LED Square Trim / Flush Lens	
5 CCT Selectable		
Model No.	Description	
LEDOOD FOOT M		
LED8SQ-5CCT-M	8" LED Square Frame / Driver connected to J-Box / 18W / 120-277V / 0-10V Dimming	



DIMMER LIST

the desired CCT.

List of 0-10V Dimmer Switch (120-277V) Dimming Rate Mfr Model # Lutron NFTV 10 - 100% Lutron NTSTV-DV 10 - 100% CD4FBLW 10 - 100% Legrand Leviton 1P710-DL 10 - 100%

CHINA : SHAOGANGTOU DISTRICT, QIAOTOU TOWN, DONGGUAN CITY, GUANGDONG 523536 E-mail : Itech@vip.163.com TEL: 86-769-83423455 / FAX: 86-769-83423173

TEL: 82-2-2666-2917~8 / FAX: 82-2-2666-7052

KOREA : A-1804, WOOLIM BLUE NINE, 240-21, YEOMCHANG-DONG, GANGSEO-GU, SEOUL, 157-779 E-mail : Itech77@Itechcorp.com