# L - TECH®

# LED350ICA / LED350ICA-01V



# Dimensions 5 ½" -3 ½" 6"

# **SPECIFICATION**

### **Plaster Frame**

 Galvanized steel construction. The housing can be removed from plaster frame to provide access to the junction box

### **Junction Box**

- Listed for through branch circuit wiring
- Contains seven 7/8" knockouts and four Romex pryouts with strain relief

# Bar Hanger

- Pre-installed Real nail easily installs in regular lumber, engineered lumber
- Bar Hangers are adjustable from 13-5/8" to 25" and can be repositioned 90 degree on plaster frame

# Listings


- cULus Listed for Damp Location
- cULus Listed for Feed Through
- Certified under ASTM-E283 for Air tight construction

# **CONNECTOR**

# **LED350ICA**Triac Dimming Ver.



# **LED350ICA-01V** 0-10V Dimming Ver.



# ORDERING INFORMATION

Model No.	Dimming	Description
LED350ICA	Triac Dimming	3.5" IC Air-Tight Dedicated New construction Housing
LED350ICA-01V	0-10V Dimming	3.5" IC Air-Tight Dedicated New construction Housing

# **COMPATIBLE TRIMS**

# LED350ICA Model NO.

LRKT3571
LRKT35XX Series
LRKT3571-3CCT
LRKT35XX-3CCT Series
LRKT3571-5CCT
LRKT35XX-5CCT Series

# Description

3.5 & 3.7 inch LED Round Gimbal Retrofit kit
3 & 3.5 & 3.7 inch LED All Retrofit kit Series
3.5 & 3.7 inch Selectable 3 CCT LED Round Gimbal Retrofit kit
3 & 3.5 & 3.7 inch Selectable 3 CCT LED All Retrofit kit Series
3.5 & 3.7 inch Selectable 5 CCT LED Round Gimbal Retrofit kit
3 & 3.5 & 3.7 inch Selectable 5 CCT LED Round Gimbal Retrofit kit
3 & 3.5 & 3.7 inch Selectable 5 CCT LED All Retrofit kit Series

# LED350ICA-01V Model NO.

LRKT3571-5CCT-M LRKT35XX-5CCT-M Series

# Description

3.5 & 3.7 inch Selectable 5 CCT LED Round Gimbal Retrofit kit3 & 3.5 & 3.7 inch Selectable 5 CCT LED All Retrofit kit Series