
L - TECH®

LED400ICA / LED400ICA-01V



Dimensions



SPECIFICATION

Plaster Frame

 Galvanized steel construction. The housing can be removed from plaster frame to provide access to the junction box

Junction Box

- Listed for through branch circuit wiring
- Contains seven 7/8" knockouts
- New Cable Trap for easy instalation of Romex Cable (US Patented / China Patented)

Bar Hanger

- Pre-installed Real nail easily installs in regular lumber, engineered lumber
- Bar Hangers are adjustable from 13-5/8" to 25" and can be repositioned 90 degree on plaster frame

Listings

- cULus Listed for Damp Location
- cULus Listed for Feed Through
- Certified under ASTM-E283 for Air tight construction

CONNECTOR

LED400ICATriac Dimming Ver.



LED400ICA-01V 0-10V Dimming Ver.



Molex Ideal connector

ORDERING INFORMATION

Model No.	Dimming	Description
LED400ICA	Triac Dimming	4" IC Air-Tight Dedicated New construction Housing
LED400ICA-01V	0-10V Dimming	4" IC Air-Tight Dedicated New construction Housing

COMPATIBLE TRIMS

LED400ICA Model NO. LRKT4XX Series

LRKT4XX Series
LRKT4XX-3CCT Series
LRKT4XX-5CCT Series

LED400ICA-01V Model NO. Description

4 inch LED All Retrofit kit Series

4 inch Selectable 3 CCT LED All Retrofit kit Series 4 inch Selectable 5 CCT LED All Retrofit kit Series

Description

LRKT4XX-5CCT-M Series 4 inch Selectable 5 CCT LED All Retrofit kit Series