


LED400SICA / LED400SICA-01V



Dimensions



SPECIFICATION

Plaster Frame

 Galvanized steel construction. The housing can be removed from plaster frame to provide access to the junction box

Junction Box

- Listed for through branch circuit wiring
- Contains one 1-1/8", one 5/8", three 7/8" knockouts
- New Cable Trap for easy instalation of Romex Cable (US Patented / China Patented)

Bar Hanger

- Pre-installed Real nail easily installs in regular lumber, engineered lumber
- Bar Hangers are adjustable from 13-5/8" to 25" and can be repositioned 90 degree on plaster frame

Listings

- cULus Listed for Damp Location
- cULus Listed for Feed Through
- Certified under ASTM-E283 for Air tight construction

ORDERING INFORMATION


Model No.	Dimming	Description
LED400SICA	Triac Dimming	4" IC Air-Tight Dedicated Shallow New construction Housing
LED400SICA-01V	0-10V Dimming	4" IC Air-Tight Dedicated Shallow New construction Housing

CONNECTOR

LED400SICA Triac Dimming Ver.



LED400SICA-01V 0-10V Dimming Ver.



COMPATIBLE TRIMS

LED400SICA

Model NO. LRKT4XX Series LRKT4XX-3CCT Series LRKT4XX-5CCT Series

LED400SICA-01V Model NO.

LRKT4XX-5CCT-M Series

Description

4 inch LED All Retrofit kit Series 4 inch Selectable 3 CCT LED All Retrofit kit Series 4 inch Selectable 5 CCT LED All Retrofit kit Series

Description

4 inch Selectable 5 CCT LED All Retrofit kit Series



CHINA : SHAOGANGTOU DISTRICT, QIAOTOU TOWN, DONGGUAN CITY, GUANGDONG 523536 E-mail : Itech@vip. I 63.com TEL: 86-769-83423455 / FAX: 86-769-83423173 KOREA : A-1804, WOOLIM BLUE NINE, 240-21, YEOMCHANG-DONG, GANGSEO-GU, SEOUL, 157-779

TEL: 82-2-2666-2917~8 / FAX: 82-2-2666-7052

E-mail : Itech77@Itechcorp.com