LED500ICRA / LED500ICRA-01V

5" IC Air-Tight LED Dedicatd Remodel Housing













Dimensions





SPECIFICATION

Junction Box

- · Listed for through branch circuit wiring
- Contains one 1-1/8", six 7/8" knockouts and four Romex pryouts with strain relief

Ceiling Thickness

• Housing adjusts from 5/8" - 1 3/8" to accommodate various ceiling thickness

Remodel Clips

• Four remodel clips secure housing and accommodates 1/2" and 5/8" ceiling materials

Listings

- cULus Listed for Damp Location
- cULus Listed for Feed Through
- Certified under ASTM-E283 for Air tight construction

CONNECTOR

LED500ICRA Triac Dimming Ver.



Ideal connector

LED500ICRA-01V

0-10V Dimming Ver.



Molex connector

Ideal connector

ORDERING INFORMATION

Model No. Dimming Description LED500ICRA Triac Dimming 5" IC Air-Tight Dedicated Remodel Housing LED500ICRA-01V 0-10V Dimming 5" IC Air-Tight Dedicated Remodel Housing

COMPATIBLE TRIMS

LED500ICRA Model NO. LRKT56X Series

I RKT54X Series LRKT56X-3CCT Series LRKT54X-3CCT Series LRKT56X-5CCT Series LRKT54X-5CCT Series

LED500ICRA-01V Model NO.

LRKT56X-5CCT-M Series LRKT54X-5CCT-M Series

Description

5&6 inch LED All Retrofit kit Series 5 inch LED Square Retrofit kit Series 5&6 inch Selectable 3 CCT LED All Retrofit kit Series 5 inch Selectable 3 CCT LED Square Retrofit kit Series 5&6 inch Selectable 5 CCT LED All Retrofit kit Series 5 inch Selectable 5 CCT LED Square Retrofit kit Series

Description

5&6 inch Selectable 5 CCT LED All Retrofit kit Series 5 inch Selectable 5 CCT LED Square Retrofit kit Series