L - TECH®

LED500SICA / LED500SICA-01V

5" IC Air-Tight LED Dedicatd Sallow New construction Housing










Dimensions



SPECIFICATION

Plaster Frame

 Galvanized steel construction. The housing can be removed from plaster frame to provide access to the junction box

Junction Box

- Listed for through branch circuit wiring
- Contains seven 7/8" knockouts and four Romex pryouts with strain relief

Bar Hanger

- Pre-installed Real nail easily installs in regular lumber, engineered lumber
- Bar Hangers are adjustable from 13-5/8" to 25" and can be repositioned 90 degree on plaster frame

Listings

- cULus Listed for Damp Location
- cULus Listed for Feed Through
- Certified under ASTM-E283 for Air tight construction

CONNECTOR

LED500SICATriac Dimming Ver.



connector

LED500SICA-01V 0-10V Dimming Ver.



Molex connector

Ideal connector

ORDERING INFORMATION

Model No.	Dimming	Description
LED500SICA	Triac Dimming	5" IC Air-Tight Dedicated Shallow New construction Housing
LED500SICA-01V	0-10V Dimming	5" IC Air-Tight Dedicated Shallow New construction Housing

COMPATIBLE TRIMS

LED500SICA Model NO. LRKT56X Series

LRKT54X Series LRKT56X-3CCT Series LRKT54X-3CCT Series LRKT56X-5CCT Series LRKT54X-5CCT Series

LED500SICA-01V Model NO.

LRKT56X-5CCT-M Series
LRKT54X-5CCT-M Series

Description

5&6 inch LED All Retrofit kit Series
5 inch LED Square Retrofit kit Series
5&6 inch Selectable 3 CCT LED All Retrofit kit Series
5 inch Selectable 3 CCT LED Square Retrofit kit Series
5&6 inch Selectable 5 CCT LED All Retrofit kit Series
5 inch Selectable 5 CCT LED Square Retrofit kit Series

Description

5&6 inch Selectable 5 CCT LED All Retrofit kit Series 5 inch Selectable 5 CCT LED Square Retrofit kit Series

