

LKTC243

2" Square Baffle LED Canless Recessed Downlight



Use the switch to set the desired Watt & CCT

- Finishes



B - Black



BZ - Bronze



SN - Satin Nickel




SPECIFICATION

QUICK FEATURES

- Die-cast aluminium structure offering excellent durability and heat dissipation
- No housing required and includes pre-wired junction box with Class2 Driver
- 4 different colors : W-White / B-Black / SN-Satin Nickel / BZ-Bronze
- Use select 3 Watt & 5 CCT with switches on the Junction box
- Input voltage : **120V**, 50/60Hz - Triac dimmers
- Operating Temperature Range : -30°C ~ 40°C (-22°F ~ 104°F)
 - All values at 25°C without a dimming control in circuit -
- cUL Listed / Wet Location / Lifetime of 50,000 hours / 5 year warranty

DIMENSIONS



LIGHT SOURCE TEST TABLE

CRI 90

Wattage	2700K	3000K	3500K	4000K	5000K
08 W	730 lm	770 lm	810 lm	830 lm	820 lm
05 W	530 lm	550 lm	580 lm	590 lm	590 lm
04 W	400 lm	420 lm	430 lm	440 lm	440 lm

ORDERING INFORMATION

120V / Triac dimming / Square Baffle

• 3 Watt & 5 CCT Selectable

Model NO.	Description
LKTC243W	2" LED Canless Recessed Downlight / White
LKTC243B	2" LED Canless Recessed Downlight / Black
LKTC243SN	2" LED Canless Recessed Downlight / Satin Nickel
LKTC243BZ	2" LED Canless Recessed Downlight / Bronze

DIMMER LIST

List of Triac Dimmer Switch (120V)

Mfr	Model #	Dimming Rate
LUTRON	SCL-153P	10 - 100%
LEVITON	6633-P	10 - 100%
LEVITON	6683	10 - 100%
LEVITON	6684	10 - 100%
LEVITON	IPI06	10 - 100%
LUTRON	AY-600P	10 - 100%
LUTRON	CN-600	10 - 100%
LUTRON	D-603PH	10 - 100%
LUTRON	LGCL-153PL	10 - 100%
LUTRON	DV-603PG	10 - 100%
LUTRON	TTCL-100H	10 - 100%
LUTRON	TT-300	10 - 100%
LUTRON	DV-600P	10 - 100%
LUTRON	GL-600H	10 - 100%
LUTRON	MACL-153M	10 - 100%
LUTRON	AYCL-153P	10 - 100%
LUTRON	TG-600PHLH	10 - 100%
LUTRON	TGCL-153P	10 - 100%
LUTRON	DVCL-153PL	10 - 100%
LEGRAND	CDLV703-PW	10 - 100%
LEGRAND	D703-PTC	10 - 100%
LEGRAND	DLV703-PLA	10 - 100%
LEVITON	6674	10 - 100%
LEGRAND	HCL453PTCCCV6	10 - 100%
LEVITON	6672	10 - 100%
LEVITON	6613-P	10 - 100%
LUTRON	LGCL-153PL	10 - 100%
LUTRON	DVCL-153P	10 - 100%
LUTRON	GTJ-250M	10 - 100%
LEVITON	6631	10 - 100%
COOPER	DLC03P	10 - 100%
COOPER	9530WS	10 - 100%
LEGRAND	H703PTCCCV6	10 - 100%



L-TECH CORPORATION
www.L-Techcorp.com

CHINA : SHAO GAN TOW DISTRICT, QIAOTOU TOWN, DONGGUAN CITY, GUANGDONG 523536
TEL : 86-769-83423455 / FAX : 86-769-83423173 E-mail : ltech@vip.163.com

KOREA : A-1804, WOOLIM BLUE NINE, 240-21, YEOMCHANG-DONG, GANGSEO-GU, SEOUL 157-779
TEL : 82-2-2666-2917-8 / FAX : 82-2-2666-7052 E-mail : ltech77@ltechcorp.com