


LED Mud Plate Retrofit


4" Trimless Round & Square LED Downlight Retrofit Kit



LED Round Trimless Ver.



LED Square Trimless Ver.



SPECIFICATION

QUICK FEATURES

- Consist of 4" Round and Square trim & LED Module
- Trim and LED modules can be easily assemble and disassemble
- Adjustable gimbal offers 28-degree tilt and up to 440-degree rotation
- Dimmable to 10% with most standard triac dimmers
- Lifetime of 50,000 hours
- Damp Location
- cUL classified / ENERGY STAR qualified
- 5 year warranty

PERFORMANCE DATA

Input Voltage	120V
Frequency	50 / 60Hz
T Ambient	-30°C ~ 40°C (-22°F ~ 104°F)

(all values at 25°C without a dimming control in circuit)


LIGHT SOURCE TEST TABLE

Wattage	2700K	3000K	4000K	5000K
8 W	610 lm	640 lm	680 lm	670 lm

CRI 90

MODULE

MODULE
MODEL NO. P-LMPT-MD




Feature


- Aluminum body dissipates heat from the LED board
- Conduit quick-connect connectors facilitate installation
- Assemble with trim use Twist lock

TRIM

ROUND TRIM
MODEL NO. P-LMPT-TRRD



SQUARE TRIM
MODEL NO. P-LMPT-TRSQ




Feature


- The body of trim is made of light-weight plastic
- LED Module mounting ring can be rotated 355 degrees, tilted to 28 degrees
- 3 Tension clips pre-installed on unit for easy installation

LED MOBILE ASSEMBLY

Trim



LED Module



ORDERING INFORMATION

Model No.	Description
P-LMPT-TRRD	4" Trimless Round Trim
P-LMPT-TRSQ	4" Trimless Square Trim
P-LMPT-MD	4" Trimless LED Module
LMPT420	4" Trimless Round Trim + LED Module
LMPT440	4" Trimless Square Trim + LED Module

DIMMER LIST

List of Triac Dimmer Switch (120V)

Mfr	Model #	Dimming Rate
COOPER	DLC03P	10 - 100%
Leviton	1A1505 / 1C1605	10 - 100%
Leviton	6631 / 6633	10 - 100%
Lutron	CT-603PG / CT-600PR	10 - 100%
Lutron	DV-600PR / DV603PG	10 - 100%
Lutron	DVW-603PGH / DVCL-153P	10 - 100%
Lutron	MACL-153M / TGCL-153P	10 - 100%
Lutron	S-600PR / S-2-LH	10 - 100%

